



GENESIS OFFROAD VEHICLE RECOVERY WINCHES 9,500LB & 12,500LB

NEW GENERATION OF HULK 4X4 WINCHES

SYNTHETIC ROPE WINCHES

9,500LB **PART# HG9500S**

Available in April 2025. Pre-order today.

12,500LB **PART# HG12500S**



Unleash the untamed with the HULK 4X4 GENESIS Offroad Vehicle Recovery Winch, engineered for serious off-roaders who break boundaries and refuse to be halted by the rugged unknown. Engineered for might, precision, and unparalleled endurance, the HULK 4X4 GENESIS range is available in 9,500lb & 12,500lb winch capacities turns formidable obstacles into mere milestones.

Merging lightweight alloy construction, some of the benefits include: IP68 water and dust rating, 7.2HP motor, full 45° clock-able gearbox and 90° clock-able motor, knurled drum rope and anchor for extra rope grip, 3 versatile control box mounting options and both wireless and wired remotes. This winch is your partner against the elements. Equipped with sturdy synthetic rope and backed by an expansive spare parts list, the HULK 4X4 GENESIS Recovery Winch ensures you're always battle-ready.

With the HULK 4X4 GENESIS Recovery Winch: Challenge the wild, face adversity head-on, and never look back. Built for the bold.

POWER & PRECISION: Powered by a formidable 7.2HP wound electric motor, the 9,500lb capacity has a robust 218:1 gear ratio, whilst the 12,500lb capacity backed by a 265:1 gear ratio for when the going gets tough.

BUILD & DURABILITY: Lightweight alloy construction ensures both durability and ease of use without compromising strength.

CONTROL & CONNECTIVITY: Includes one reliable wired, and two EMC-compliant and range tested wireless remotes, ensuring versatile control in all recovery scenarios.

PROTECTION GUARANTEED: Fully IP68 water and dust rated for unbeatable protection against the elements.

UNPARALLELED LONGEVITY: Winches come fortified with a limited lifetime mechanical warranty and an exceptional 7 Year electrical warranty. To assure your journeys are uninterrupted, we've also made available an extensive list of spare parts.





ATV / UTV WINCHES SERIES

2,000LB TO POWERFUL 6,000LB MODELS

SYNTHETIC ROPE WINCHES

The new HULK 4X4 ATV/UTV Winch series ranges from sturdy 2,000LB to powerful 6,000LB models, built to move loads or conquer challenging offroad terrains.

Featuring sealed motors, advanced differential planetary gear trains, and durable 12V Permanent magnet motors for reduced power consumption, these winches ensure consistent reliability and performance.

These winches come with free spooling cam activated clutches and advanced braking systems, they offer exceptional control and safety.

Constructed with UV-resistant exteriors and sturdy winch ropes with safety latches, these winches are designed for lasting use in tough conditions.

2,000LB PART# HG2000

ESSENTIAL CAPABILITY: Offering a 2,000LB line pull with a 153:1 gear ratio, powered by a 12V DC, 1.0 HP, permanent magnet motor.

RUGGED CONSTRUCTION: Made with a sealed motor, mechanical and dynamic brake, and a UV-resistant clevis slip hook for secure, reliable recoveries.



3500LB PART# HG3500S

4500LB PART# HG4500S

VERSATILE STRENGTH: Available in 3,500lb & 4,500lb capacities, both with a 153:1 gear ratio, powered by a 12V DC, 1.0 HP, permanent magnet motor.

BUILT TO LAST: Equipped with a sealed motor, free spooling, cam activated clutch, and aluminium hawse fairlead - everything you need for challenging terrains.



6,000LB PART# HG6000S

EFFECTIVE POWER: 6,000LB capacity, 166:1 gear ratio, propelled by a 12V DC, 1.7 HP, permanent magnet motor for seamless recovery.

ENHANCED DURABILITY: Sealed motor and differential planetary gear train, along with a UV-resistant, aluminium hawse fairlead, set a new standard for reliability.



PART #	HG2000	HG3500S	HG4500S	HG6000S
Rated Line	2000lb (909kg)	3500lb (1587.5kg)	4500lb (2041kg)	6000lb (2721kg)
Motor	0.75kw, 1.0hp, 12V DC Permanent Magnet	1.2hp, 12V DC Permanent Magnet	1.4hp, 12V DC Permanent Magnet	1.7hp, 12V DC Permanent Magnet
Gearing	Differential planetary	3-Stage Planetary	3-Stage Planetary	3-Stage Planetary
Gear Ratio	153:1	153:1	166:1	166:1
Free Spooling	Pull & Turn	Cam Activated	Cam Activated	Cam Activated
Wire Rope	4.8mm x 15.2m	5mm x 15m	5.5mm x 15m	6mm x 15m
Size: L x W x H	285 x 105 x 105mm	285 x 100 x 106mm	335 x 114 x 120mm	400 x 116 x 119mm